



Detailed Specifications & Technical Data



5100UP Non-Paired - Commercial Audio Systems - 2 Conductors Cabled

		<p>For more information please call 1-800-Belden1</p> <p><u>See Put-ups and Colors</u></p>
---	--	---

Description:

14 AWG bare high-conductivity ETP copper conductors, highly stranded for ultra flexibility, high-grade PVC insulation, PVC jacket with ripcord, sequential footage marking every two feet.

PHYSICAL CHARACTERISTICS:

CONDUCTOR:

Number of Conductors	2
Total Number of Conductors	2
AWG	14
Stranding	42
Conductor Material	Bare High-Conductivity ETP Copper

INSULATION:

Insulation Material	PVC - Polyvinyl Chloride
Nom. Insulation Wall Thickness	.020 in.

OVERALL CABLING:

Overall Cabling Lay Length	3.5 in.
Overall Cabling Twists/ft.	3.4
Overall Cabling Color Code Chart	Black, White

OUTER SHIELD:

Outer Shield Material	Unshielded
-----------------------	------------

OUTER JACKET:

Outer Jacket Material	PVC - Polyvinyl Chloride
Outer Jacket Nominal Wall Thickness	.015 in.
Outer Jacket Ripcord	Yes

OVERALL NOMINAL DIAMETER:

Overall Nominal Diameter	.260 in.
--------------------------	----------

MECHANICAL CHARACTERISTICS:

Operating Temperature Range	-20°C To +75°C
UL Temperature Rating	75°C
Bulk Cable Weight	39 lbs/1000 ft.
Max. Recommended Pulling Tension	109.2 lbs.

Detailed Specifications & Technical Data



5100UP Non-Paired - Commercial Audio Systems - 2 Conductors Cabled

Min. Bend Radius (Install)	2.5 in.
----------------------------	---------

APPLICABLE SPECIFICATIONS AND AGENCY COMPLIANCE:

APPLICABLE STANDARDS:

NEC/(UL) Specification	CL3
EU CE Mark (Y/N)	Yes
EU RoHS Compliant (Y/N)	Yes
EU RoHS Compliance Date (mm/dd/yyyy):	04/01/2005

FLAME TEST:

UL Flame Test	UL1685 UL Loading
---------------	-------------------

PLENUM/NON-PLENUM:

Plenum (Y/N)	N
--------------	---

ELECTRICAL CHARACTERISTICS:

Nom. Inductance	0.17 μ H/ft
Nom. Capacitance Conductor to Conductor @ 1 KHz	29 pF/ft
Nom. Conductor DC Resistance @ 20 Deg. C	2.42 Ohms/1000 ft
Max. Operating Voltage - UL	300 V RMS
Max. Recommended Current	22 Amps per conductor @ 25°C

PUT-UPS AND COLORS:

Item	Description	Put-Up (ft.)	Ship Weight (lbs.)	Jacket Color	Notes
5100UP 0051000	2 #14 PVC FRPVC	1000	43	GREEN, DARK	
5100UP 005500	2 #14 PVC FRPVC	500	22.5	GREEN, DARK	
5100UP 005U1000	2 #14 PVC FRPVC	U1000	41	GREEN, DARK	
5100UP 005U500	2 #14 PVC FRPVC	U500	21	GREEN, DARK	
5100UP 0081000	2 #14 PVC FRPVC	1000	43	GRAY	C
5100UP 008500	2 #14 PVC FRPVC	500	22.5	GRAY	
5100UP 008U1000	2 #14 PVC FRPVC	U1000	41	GRAY	
5100UP 008U500	2 #14 PVC FRPVC	U500	21	GRAY	
5100UP 0091000	2 #14 PVC FRPVC	1000	43	WHITE	
5100UP 009500	2 #14 PVC FRPVC	500	22.5	WHITE	
5100UP 009U1000	2 #14 PVC FRPVC	U1000	41	WHITE	
5100UP 009U500	2 #14 PVC FRPVC	U500	21	WHITE	

Detailed Specifications & Technical Data



5100UP Non-Paired - Commercial Audio Systems - 2 Conductors Cabled

5100UP 0101000	2 #14 PVC FRPVC	1000	43	BLACK	C
5100UP 010500	2 #14 PVC FRPVC	500	22.5	BLACK	
5100UP 010U1000	2 #14 PVC FRPVC	U1000	41	BLACK	
5100UP 010U500	2 #14 PVC FRPVC	U500	21	BLACK	
5100UP D151000	2 #14 PVC FRPVC	1000	43	BLUE	C
5100UP D15500	2 #14 PVC FRPVC	500	22.5	BLUE	C
5100UP D15U1000	2 #14 PVC FRPVC	U1000	41	BLUE	
5100UP D15U500	2 #14 PVC FRPVC	U500	21	BLUE	

C = CRATE REEL PUT-UP.

Revision Number: 1 Revision Date: 10-05-2005

© Copyright 2006 Belden, Inc
All Rights Reserved.

Although Belden ("Belden") makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described herein are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with the following environmental regulations: California Proposition 65 Consent Judgment For Wire & Cable Mfgs.(San Francisco Superior Court Nos. 312962 And 320342); EU RoHS (Directive 2002/95/EC, 27-Jan-2003);Material manufactured prior to the compliance date may still be in stock at Belden facilities and in our Distributor's inventory. EU ELV (Directive 2000/53/EC, 18-Sept-2000); EU WEEE (Directive 2002/96/EC, 27-Jan-2003); And EU BFR (Directive 2003/11/EC, 6-Feb-2003). The information provided in this Product Disclosure, and the identification of materials listed as reportable or restricted within the Product Disclosure, is correct to the best of Belden's knowledge, information and belief at the date of its publication. The information provided in the Product Disclosure is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. This Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.

Belden declares this product to be in compliance with EU LVD (Low Voltage Directive 73/23/EEC), as amended by directive 93/68/EEC.